

Fingerprint Mifare S50 RFID Contactless Card



FPrfid-S50 is a powerful 13.56Mhz Mifare S50 RFID card built-in capacitive fingerprint sensor with MCU embedded recognition algorithms. The Cermet-like coating of fingerprint sensor provides up to 6H hardness and protects sensors against scratch, impact and daily wear-and-tear. It can be widely applied in various fields such as access control systems, locks and safes, high-level security applications. With software of fingerprint enrollment, administrator can easily manage fingers enrollment.

SPECIFICATION		
Mifare RFID Card		
Card Size	85.6 (L) x 54 (W) x 0.74 ~ 0.84 (T) mm	
chipset	Philips MF1 IC S50	
Frequency	HF 13.56Mhz	
Card Material	ABS, PVC, PET as requested	
LED Indicators	2 LEDs, red indicates power on; green indicates fingerprint recognition	
Embedded Battery	Solid state battery for fingerprint sensor	
Card Warping/ Curl Test	Compliance ISO/IEC 14443-1 4.3.3, ISO/IEC 10373-1 5.8	
Capacitive FingerPrint Sensor		Charger for Fingerprint RFID Card
Resolution / Sensing Area	508 DPI / 8 x 8 mm or 160 x 160 pixel	
Sensor Type	Capacitance Type	
Supply Voltage	3.0 ~ 3.6VDC	
Hardness / Surface	Up to 6H / Cermet-like Coating	
FAR / FRR	0.0001 / < 2%	
Fingerprint Template Number	Finger number x 5, each finger image x 8	
Battery Life	300 times operation based on 6 sec. when pressing power button	
Operating Temperature	-10 ~ 50° C / < RH 20 ~ 85%	

APPLICATION SOFTWARE OF FINGERPRINT ENROLLMENT





^{*} Features and specification are subject to change without notice.





10 Fl., No. 61, Yan-Ping S. Rd., Taipei 100, Taiwan TEL: +886 2 2311 3299 Email: info@digimore.com.tw

